Parts and Accessories Service and Repairs Resource Center Team NAPA

Current Vehicle

Change Vehicle

Search Catalog

Keyword

GO

NAPA Part No.

Non-NAPA Part No.

GO GO

Right parts for the job

Job Type Search

NAPA Locator

Enter Zip

Parts Store Repair Shop Collision Center Truck Center

My Account



Create Account



Click here to apply for the NAPA VISA[©] Card

IMA .

Material Safety Data Sheet (MSDS)

Disc Brake Quiet

MATERIAL SAFETY DATA SHEET

Effective Date: none Revision Date: none

Disc Brake Quiet

Code: SD Page: 1

Section 1 - Product and Company Identification

PRODUCT NAME: Disc Brake Quiet

MANUFACTURER'S NAME: EMERGENCY TELEPHONE NUMBER Specialty Division (216)566-2917

26300 Fargo Avenue

Bedford Heights, OH 44146 MISCELLANEOUS INFORMATION

Section 2 - Hazardous Ingredients

INGREDIENT CAS NO.	% BY WT.	ACGIH TLV	OSHA PEL	UNITS	V.P.
Propane	8		1000	PPM	760.00
74-98-6 Butane	22	800	800	PPM	760.00
106-97-8					
Toluene	8	50	100	PPM(skin)	22.00
108-88-3	STEL		150 E	PPM(skin)	
Acetone	32	750	750	PPM	180.00
67-64-1	STEL	1000	1000 E	PPM	
Methyl Ethyl Ketone	15	200	200	PPM	70.00
78-93-3	STEL	300	300 E	PPM	

MATERIAL SAFETY DATA SHEET Effective Date: none Disc Brake Quiet

Code: SD Page: 2

Revision Date: none

Section 3 - Hazards Indentification

ROUTES OF EXPOSURE: Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE HEALTH HAZARDS:

CHRONIC HEALTH HAZARDS: No ingredient in this product is an IARC, NTP, or OSHA listed carcinogen. Methyl Ethyl Ketone may increase the nervous system efects of other solvents.Prolonged overexposure to solvent ingredients in Section II may cause adverse effects to the liver, urinary, cardiovascular and reproductive systems. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

EFFECTS OF OVEREXPOSURE: Irritation of eyes, skin, and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Headache, dizziness, nausea, and loss of coordination are indications of excesive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None generally recognized.

Section 4 - First Aid Measures

EMERGENCY AND FIRST AID PROCEDURES:

 $\mbox{ IF INHALED: } \mbox{ If affected, remove from exposure. } \mbox{ Restore breathing. } \mbox{ Keep} \\ \mbox{ warm and quiet.}$

 $\mbox{IF ON SKIN:}\ \mbox{Wash affected area thoroughly with soap and water.}\ \mbox{Remove contaminated clothing and launder before re-use.}$

IF IN EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

IF SWALLOWED: Get medical attention.

MATERIAL SAFETY DATA SHEET

Effective Date: none Revision Date: none

Disc Brake Quiet

Code: SD Page: 3

Section 5 - Firefighting Measures

FLASH POINT (Method Used): Propelant < 0 F

FLAMMABLE LIMITS:

LEL: 1.0 UEL: 12.8

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS: Isolate from heat, eletrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES: Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section 6 - Environmental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Ventilate and remove with inert absorbent.

Section 7 - Handling and Storage

DOL STORAGE CATEGORY: 1A

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off

stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS: Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

MATERIAL SAFETY DATA SHEET

Effective Date: none

Disc Brake Quiet

Code: SD

Page: 4 ______

Section 8 - Exposure Controls/Personal Protection

PRECAUTIONS TO BE TAKIN IN USE: Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

VENTILATION: Local exhaust preferable. General exhaust acceptable if the exposure to mateials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION: If personal exposure cannot be controlled below applicable limts by ventilation, wear a properly fitted organic $\verb|vapor/particulate| respirator approved by \verb|NIOSH/MSHA| for protection| \\$ against materials in Section II.

PROTECTIVE GLOVES: None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EYE PROTECTION: Wear safety specacles with unperforated sideshields.

Section 9 - Physical and Chemical Properties

PRODUCT WEIGHT..... 6.05 lb./gal. SPECIFIC GRAVITY..... 0.73

VOLATILE VOLUME..... 91%

VOLATILE WEIGHT...... 86.75% (Less Federally Exempt Solvents)

HMIS..... 2 4 0

 ${\tt EVAPORATION} \ {\tt RATE......} \ {\tt Faster} \ {\tt than} \ {\tt Ether}$ VAPOR DENSITY..... Hevier than Air

MELTING POINT..... N.A. SOLUBILITY IN WATER..... N.A.

Section 10 - Stability and Reactivity

STABILITY: Stable

CONDITIONS TO AVOID: None known

INCOMPATABILITY(Materials to Avoid): None known

HAZARDOUS DECOMPOSITION PRODUCTS: By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION: Will not occur

Section 11 - Toxicological Information

Not available.

MATERIAL SAFETY DATA SHEET Effective Date: none Disc Brake Quiet

Revision Date: none

Revision Date: none

Code: SD Page: 5

Section 12 - Ecological Information

Not available.

Section 13 - Disposal Considerations

WASTE DISPOSAL METHOD: Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to detemine the applicable $\ensuremath{\mathtt{EPA}}$ hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section 14 - Transport Information

Not available.

Section 15 - Regulatory Information

SARA 313 (40 CFR 372.65c) SUPPLIER NOTIFICATION

CALIFORNIA PROPOSITION 65: This product contains chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

Cartier 16 Other Triangulies

Section 16 - Other Information

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Return to previous page.

Return to top of page.

©2002, National Automotive Parts Association
This site is best viewed using <u>JavaScript-enabled</u> Internet Explorer Version 5.0 and above.

For best printing results, please use Internet Explorer.