

MATERIAL SAFETY DATA SHEET

1 SPEEDBALL Heavy Duty Spray Cleaner Ready-to-Use MSDS Ref. No: 4044 RTU Date Prepared: 06/25/2003 Date Revised: 06/25/2003

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME/USE: 1 SPEEDBALL Heavy Duty Spray Cleaner Ready-to-Use

A 1:6 dilution of 1 SPEEDBALL Heavy Duty Spray Cleaner Concentrate

Product Synonyms: Command Center 1 SPEEDBALL Heavy Duty Spray Cleaner Ready-to-Use

A 1:6 dilution of Command Center 1 SPEEDBALL Heavy Duty Spray Cleaner Concentrate;

Outpost 1 SPEEDBALL Heavy Duty Spray Cleaner Ready-to-Use

A 1:6 dilution of Outpost 1 SPEEDBALL Heavy Duty Spray Cleaner Concentrate;

Command Center HEAVY DUTY SPRAY CLEANER Ready-to-Use 1

A 1:6 dilution of Command Center HEAVY DUTY SPRAY CLEANER Concentrate 1

MANUFACTURER

 The Butcher Company
 Butcher Telephone Number:
 800-225-9475

 8310 16th St.
 Emergency Telephone (24 hours):
 800-228-5635

 Sturtevant, WI 53177-0902
 CHEMTREC (U.S./Can.):
 800-424-9300

 CHEMTREC (Int'l):
 +1 703-527-3887

2. COMPOSITION / INFORMATION ON INGREDIENTS

 INGREDIENT(S)
 CAS#
 % BY WEIGHT

 2-Butoxyethanol
 111-76-2
 5 - 7

 Ethanolamine
 141-43-5
 1 - 3

See Section 8 for Exposure Limits NA - Not Applicable

OSHA REGULATORY STATUS: This product is classified as hazardous under OSHA regulations.

WHMIS CLASS: Class D- Division 2B

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Clear, Purple Liquid . Mild Odor. Causes Eye Irritation.

POTENTIAL HEALTH EFFECTS (See Section 11 for Toxicological Information)

PRIMARY ROUTE(s) OF EXPOSURE: \underline{X} Eye \underline{X} Skin Contact \underline{X} Skin Absorption

X Inhalation X Ingestion

EFFECTS OF ACUTE EXPOSURE

EYES: Causes eye irritation. Symptoms may include redness and pain.

SKIN: May cause mild skin irritation. Symptoms may include redness.

INHALATION: High concentrations of vapor or mist may cause nose, throat and respiratory tract irritation. Symptoms may include

coughing

INGESTION: May cause mouth, throat and stomach irritation. Symptoms may include nausea, vomiting and diarrhea. May also cause central nervous system effects including headache, dizziness and weakness.

EFFECTS OF CHRONIC EXPOSURE: Prolonged or repeated contact may cause skin irritation.

MEDICAL CONDITIONS AGGRAVATED: May aggravate pre-existing eye, skin and respiratory conditions.

4. FIRST AID MEASURES

EYES: Flush eyes with plenty of water while holding eyelids apart. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Do not put any medication in the victim's eyes unless instructed by a physician. Get medical attention.

SKIN: Flush with water, then wash with soap and water. Remove saturated clothing. Get medical attention if irritation develops.

INHALATION: Remove to fresh air. If not breathing, give respiration; if breathing is difficult, give oxygen (by trained personnel only). Get medical attention if symptoms persist.

INGESTION: Do not induce vomiting. Drink large quantities of water. Get immediate medical attention. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

FLASH POINT AND METHOD: > 93°C (200°F)TCC

FLAMMABLE LIMITS: Not applicable.

AUTOIGNITION TEMPERATURE: Not applicable.

EXTINGUISHING MEDIA: Use extinguishing media appropriate for surrounding fire.

HAZARDOUS COMBUSTION PRODUCTS: Normal products of combustion (carbon monoxide and carbon dioxide).

FIRE AND EXPLOSION HAZARDS: None known.

FIRE FIGHTING INSTRUCTIONS: This product is not flammable. As in any fire, MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear should be worn.

6. ACCIDENTAL RELEASE MEASURES

See Section 8, Exposure Controls/Personal Protection and Section 3, Hazard Identification. Floors may be slippery. Use care to avoid falling. Contain and isolate spill. Keep non-essential personnel from entering spill area. Use mop, absorbent, or wet vacuum to collect material for proper disposal. Rinse area with water.

7. HANDLING AND STORAGE

HANDLING: Follow label use directions. Do not mix with other chemicals unless instructed by label directions. Avoid contact with eyes and skin. Wash thoroughly after handling. Remove saturated clothing. Wash clothing and equipment before reuse.

STORAGE: Keep container closed when not in use. Store away from incompatible materials. (See Section 10, Stability and Reactivity).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT (PPE)

EYE: Where eye contact is possible, wear safety glasses with side shields or chemical splash goggles (ANSI Z87.1 approved).

SKIN: Where prolonged or repeated contact is possible, chemical-resistant clothing (e.g., gloves) is recommended.

RESPIRATORY: No respiratory protection is required if ventilation is adequate.

ENGINEERING CONTROLS: Good general room ventilation is expected to be adequate. If user operations generate vapor or mist, ventilation

should be used to keep airborne concentrations below exposure limits.

EXPOSURE LIMITS:

INGREDIENT(S) OSHA PEL/STEL ACGIH TLV/STEL 2-Butoxyethanol

25 ppm 120 mg/m3 / 25 ppm 121 mg/m3 /

Skin

Ethanolamine 3 ppm 8 mg/m3 / 3 ppm 7.5 mg/m3 /

6 ppm 15 mg/m3 6 ppm 15 mg/m3

NA - Not Available

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Mild

APPEARANCE: Clear, Purple

pH: 12.5

PERCENT VOLATILE BY WEIGHT: 98 VAPOR PRESSURE: Not Available VAPOR DENSITY: Not Available **BOILING POINT:** Not Available

FREEZING/MELTING POINT: Not Available

SOLUBILITY IN WATER: Complete **EVAPORATION RATE**: Not Available

SPECIFIC GRAVITY: 1.01 VISCOSITY: Water Thin

OCTANOL/WATER PARTITION COEFFICIENT: Not Available

ODOR THRESHOLD: Not Available

10. STABILITY AND REACTIVITY

STABILITY (CONDITIONS TO AVOID): Stable.

POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION: None known.

INCOMPATIBLE MATERIALS: Strong acids (e.g., hydrochloric) and oxidizers (e.g., bleach).

11. TOXICOLOGICAL INFORMATION

ACUTE DATA: This product is a moderate to severe eye irritant and a mild skin irritant. Based on acute toxicity testing, it is not considered to be toxic by inhalation, ingestion, or skin absorption. Acute overexposure to high concentrations of 2-butoxyethanol by skin absorption, ingestion and inhalation has caused blood, liver and kidney effects in laboratory animals. The following additional data are available for this product and its ingredients:

PRODUCT/INGREDIENT ORAL LD₅₀ (rat) DERMAL LD₅₀ (rabbit) INHALATION LC₅₀ (rat)

1 SPEEDBALL Heavy Duty Spray Cleaner Ready-to-Use >200 mg/L (1-hr) >5000 mg/kg >1000 mg/kg 2-Butoxyethanol 470 - mg/kg 220 - mg/kg 450 - ppm (4-hr) 1720 - mg/kg 1018 - mg/kg Ethanolamine Not Available

SENSITIZATION DATA: No data available.

CHRONIC DATA:

Prolonged overexposure to high concentrations of ethanolamine by inhalation and ingestion has caused liver and kidney effects in laboratory animals. Prolonged overexposure to high concentrations of 2-butoxyethanol by skin absorption, ingestion and inhalation has caused blood, liver and kidney effects in laboratory animals.

REPRODUCTIVE/TERATOGENIC DATA: No data available.

CARCINOGENIC/MUTAGENIC DATA: Not listed as carcinogenic by NTP, IARC, or ACGIH or regulated as a carcinogen by OSHA.

SYNERGISTIC MATERIALS: No data available.

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

Disposal of this material should be in accordance with local, state or provincial and federal regulations. The unused product, at its recommended use dilution, is a RCRA hazardous waste (Corrosive-D002) in accordance with 40 CFR 261. The product has not been evaluated by the Toxicity Characteristic Leachate Procedure (TCLP). According to RCRA, it is the responsibility of the waste generator to ensure proper disposal.

14. TRANSPORT INFORMATION

DOT/TDG HAZARDOUS MATERIAL DESCRIPTION: Not regulated

15. REGULATORY INFORMATION

Not meant to be all-inclusive---selected regulations represented.

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Under 40 CFR 370.2, this product meets the following hazard categories: Immediate, Delayed.

313 REPORTABLE INGREDIENTS: 2-Butoxyethanol is subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 under the chemical category Glycol Ethers.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: Not reportable under CERCLA.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: This product complies with all TSCA inventory requirements.

MASSACHUSETTS, NEW JERSEY, PENNSYLVANIA RIGHT-TO-KNOW:

INGREDIENT(S)	CAS NO.	STATE LISTING
Water	7732-18-5	Not Listed
2-Butoxyethanol	111-76-2	MA, NJ, PA
Ethanolamine	141-43-5	MA, NJ, PA

NA - Not Applicable

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): Class D-Division 2B, eye irritant; Class D-Division 2B, chronic toxic effects. This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.


16. OTHER INFORMATION

HMIS RATING

HEALTH	*	2
FLAMMABILITY		0
REACTIVITY		0
PERSONAL PROTECTION		-

APPROVED BY: EH&S/Regulatory Affairs

NFPA CODES:



MSDS STATUS

Revision No: 3

Revision #: 3

This MSDS replaces the October 19, 2000 MSDS. Any changes in information are as follows: In Section 1

Date Prepared

APPROVAL DATE: 06/25/2003

The information on this data sheet represents our current data and best opinion as to the proper use in handling of the product under normal foreseeable conditions. Any use of this product which is not in conformance with this data sheet or product label, or which involves using the product in combination with any other product or any other process is the responsibility of the user.