

# MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

## IDENTITY AND DISTRIBUTOR'S INFORMATION

<b>NFPA Rating:</b> Health-2; Flammability-3; Reactivity-0; Special-0 <b>Manufactured For:</b> WAXIE Sanitary Supply <b>Address:</b> 9353 Waxie Way San Diego, CA 92193-1036 <b>Phone:</b> 1-800-995-4466	<b>HMIS Rating:</b> Health-2; Flammability-3; Reactivity-0; Personal Protection-B <b>DOT Hazard Classification:</b> ORM-D <b>Identity (trade name as used on label):</b> Jelled Rite-Away Vandalism Mark Remover <b>MSDS Number:</b> A00179 <b>Revision -</b> 17 Information Calls: 858-292-8111 <b>Date Prepared:</b> 12/06/01 <b>Prepared By:</b> CH/TR
<b>EMERGENCY RESPONSE NUMBER:</b> 1-800-255-3924 <b>NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA</b>	

## SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION

COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
ETHYL ALCOHOL	64-17-5	No	1000	1000	d
TOLUENE	108-88-3	Yes	200	100	d
ACETONE	67-64-1	No	1000	750	d
ISOPROPYL ALCOHOL	67-63-0	No	400	400	d
2-BUTOXYETHANOL *	111-76-2	Yes	25 (skin)	20 (skin)	d
ISOBUTANE / PROPANE BLEND	75-28-5	No	800	800	d
METHANOL	74-98-6	No	1000	1000	d
*GLYCOL ETHER	67-56-1	Yes	200	200	d
<b>WARNING:</b> This product contains a chemical or chemicals known to the State of California to cause birth defects or other reproductive harm.					

## SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS

<b>Boiling Point:</b> N/A	<b>Specific Gravity (H2O=1):</b> Concentrate Only = 0.81
<b>Vapor Pressure:</b> PSIG @ 70°F (Aerosols): Max.60	<b>Vapor Pressure (Non-Aerosols)(mm Hg and Temperature):</b> N/A
<b>Vapor Density (Air = 1):</b> N/E	<b>Evaporation Rate ( = 1):</b> N/E
<b>Solubility in Water:</b> Soluble	<b>Water Reactive:</b> No
<b>Appearance and Odor:</b> Clear gel, aromatic solvent odor.	

## SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

<b>FLAMMABILITY</b> as per USA FLAME PROJECTION TEST (aerosols) <b>EXTREMELY FLAMMABLE</b>	<b>Auto Ignition Temperature:</b> N/E	<b>Flammability Limits in Air by % in Volume:</b> % LEL: N/E      % UEL: N/E
<b>FLASH POINT AND METHOD USED (non-aerosols):</b> N/A	<b>EXTINGUISHER MEDIA:</b> Foam, dry chemical, carbon dioxide, water fog.	
<b>SPECIAL FIRE FIGHTING PROCEDURES:</b> Self-contained breathing apparatus.		
<b>Unusual Fire &amp; Explosion Hazards:</b> Do not expose aerosols to temperatures above 130°F or the container may rupture.		

## SECTION 4 - REACTIVITY HAZARD DATA

<b>STABILITY</b> [ X ] STABLE [ ] UNSTABLE	<b>HAZARDOUS POLYMERIZATION</b> [ ] WILL [ X ] WILL NOT OCCUR
<b>Incompatibility (Mat. to avoid):</b> Acids and strong oxidizers.	<b>Conditions to Avoid:</b> Open flame, welding arcs, heat, sparks.
<b>Hazardous Decomposition Products:</b> CO, CO2.	

## SECTION 5 - HEALTH HAZARD DATA

<b>PRIMARY ROUTES OF ENTRY:</b> [ X ] INHALATION [ ] INGESTION [ X ] SKIN ABSORPTION [ ] EYE [ ] NOT HAZARDOUS	
<b>ACUTE EFFECTS:</b>	
<b>Inhalation:</b> Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.	<b>Skin Contact:</b> Irritation
<b>Eye Contact:</b> Irritation	
<b>Ingestion:</b> Possible chemical pneumonitis if aspirated into lungs. Nausea.	
<b>CHRONIC EFFECTS:</b> (Effects due to excessive exposure to the raw materials of this mixture) May cause cardiac abnormality, liver abnormalities, kidney and/or liver damage. Lab animals have experienced anemia, liver, kidney, lung, blood damage to Glycol Ether EB.	
<b>Medical Conditions Generally Aggravated by Exposure:</b> May aggravate existing eye, skin, or upper respiratory conditions.	

## EMERGENCY FIRST AID PROCEDURES

<b>Eye Contact:</b> Flush with water for 15 minutes. If irritated, seek medical attention.
<b>Skin Contact:</b> Wash with soap and water. If irritated, seek medical attention.
<b>Inhalation:</b> Remove to fresh air. Resuscitate if necessary. Get medical attention.
<b>Ingestion:</b> DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.

## SECTION 6 - CONTROL AND PROTECTIVE MEASURES

<b>Respiratory Protection (specify type):</b> If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.
<b>Protective Gloves:</b> Rubber gloves. <b>Eye Protection:</b> Safety glasses recommended.
<b>Ventilation Requirements:</b> Adequate ventilation to keep vapor concentration below TLV.
<b>Other Protective Clothing &amp; Equipment:</b> None
<b>Hygienic Work Practices:</b> Wash with soap and water before handling food. Remove contaminated clothing.

## SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

<b>Steps To Be Taken If Material Is Spilled Or Released:</b> Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations. Prevent from entering drains and sewer.
<b>Waste Disposal Methods:</b> Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.
<b>Precautions To Be Taken In Handling &amp; Storage:</b> Do not puncture or incinerate containers. Do not store at temperatures above 130°F.
<b>Other Precautions &amp;/or Special Hazards:</b> KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Remove ignition sources.

*We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.*

\*\* Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only