

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number CO0020
Product name **Satin Premium Furniture Polish**
Effective date 10-Aug-2012
Company information Brady Industries
Las Vegas, NV 89118 United States
Company phone General Assistance 702-876-3990
Emergency telephone US 1-866-836-8855
Emergency telephone outside US 1-952-852-4646
Version # 01
Product use Furniture polish

2. Hazards Identification

Emergency overview Aerosol. CONTENTS UNDER PRESSURE.
Potential health effects
Eyes Health injuries are not known or expected under normal use.
Skin Health injuries are not known or expected under normal use.
Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.
Ingestion Exposure by ingestion of an aerosol is unlikely.
Target organs Central nervous system.
Chronic effects May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage.
Signs and symptoms Narcosis.

3. Composition / Information on Ingredients

Components	CAS #	Percent
n-Butane	106-97-8	1 - 3
Propane	74-98-6	1 - 3
Non-hazardous and other components below reportable levels		> 90

4. First Aid Measures

First aid procedures
Eye contact Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
Skin contact Rinse with water. Get medical attention if irritation develops and persists.
Inhalation If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Ingestion In the unlikely event of swallowing contact a physician or poison control center.
Notes to physician Symptoms may be delayed.

5. Fire Fighting Measures

Flammable properties Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.
Extinguishing media
Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Protection of firefighters
Protective equipment and precautions for firefighters In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up.

6. Accidental Release Measures

Methods for containment	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.
Methods for cleaning up	Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

7. Handling and Storage

Handling	Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Avoid prolonged exposure.
Storage	Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Avoid exposure to long periods of sunlight. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 1 Aerosol (NFPA 30B)

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS #	TWA	STEL	Ceiling
n-Butane	106-97-8	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

OSHA

Components	CAS #	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established

Personal protective equipment

Eye / face protection	Not normally needed.
Skin protection	No special protective equipment required.
Respiratory protection	No personal respiratory protective equipment normally required. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance	Film.
Boiling point	188.6 °F (87.2 °C) estimated
Color	White.
Density	0.9667 g/cm3 estimated
Flammability (HOC)	4.2926 kJ/g estimated
Flash back	No
Flash point	-156 °F (-104.4 °C) estimated
Form	Aerosol.
Freezing point	Not available
Odor	fruity
pH	10 - 11
Physical state	Liquid.
Pressure	65 - 85 psig @ 70F
Solubility	Completely
Specific gravity	0.9668 estimated

10. Chemical Stability & Reactivity Information

Conditions to avoid	Heat, flames and sparks.
Incompatible materials	None known.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological Information

Acute effects	Acute LC50: 3311 mg/l/4h estimated, Rat, Inhalation Acute LD50: 26282 mg/kg estimated, Rat, Dermal
---------------	---

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

n-Butane	106-97-8	Inhalation LC50 Rat 658 mg/L 4 h
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h

Sensitization	Not expected to be hazardous by OSHA criteria.
Teratogenicity	Not expected to be hazardous by OSHA criteria.

12. Ecological Information

Ecotoxicity	LC50 3429 mg/L, Fish, 96.00 Hours, EC50 26718 mg/L, Daphnia, 48.00 Hours, Contains a substance which causes risk of hazardous effects to the environment.
-------------	---

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F
Disposal instructions	Contents under pressure. Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Aerosols
Hazard class	2.1
UN number	UN1950

Additional information:

Special provisions	153, N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

Further information	This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2013, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/13 and may be used now in place of the "Consumer Commodity ORM-D" marking but not concurrently.
---------------------	---



IMDG

Basic shipping requirements:

Proper shipping name	AEROSOLS
Hazard class	2.1
UN number	1950

Additional information:

Packaging exceptions	LTD QTY
Item	5F
Labels required	None
Transport Category	2



IATA**Basic shipping requirements:**

Proper shipping name Aerosols, flammable
Hazard class 2.1
UN number 1950
Additional information:
Packaging exceptions LTD QTY
Labels required 2.1



15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Hazard categories (311/312) Immediate Hazard - Yes
 Delayed Hazard - No
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

n-Butane	106-97-8	Present
Propane	74-98-6	Present

16. Other Information

Further information

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 1
 Flammability: 2
 Physical hazard: 0
 Personal protection:

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication, The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification, The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Prepared by

Regulatory Compliance