

SECTION I

PRODUCT CODE NUMBER _____ TLV _____
 MANUFACTURER'S NAME Majestic Wax Company EMERGENCY INFORMATION day 303-355-1606
night 303-722-8081-303-680
 MANUFACTURER'S ADDRESS 6035 E. 38th Ave., Denver, Colorado 80207
 PRODUCT Velva-Sheen COMMON NAME _____
 GENERIC NAME _____ CHEMICAL NAME _____
 CHEMICAL FAMILY _____ DOT PROPER SHIPPING NAME _____
 WARNING STATEMENTS _____

SECTION II - INGREDIENTS

	%	TLV
Mineral Oil	49.9	Not Determined
Hydrocarbon Solvent*	49.9	500ppm

(*Solvent is a complex mixture of paraffin, isoparaffin, naphthene and aromatic hydrocarbons in the C₁₁ to C₁₅ carbon number range).

* Threshold limit value set by (A) DSHA, (B) ACGIH, (C) See Section III, (O) Other, (NE) Not Established (Units are in PPM unless otherwise specified)

SECTION III - PHYSICAL DATA

APPROXIMATE BOILING RANGE: 500°F VAPOR PRESSURE: less than 1mm
 VAPOR DENSITY: Not Determined SOLUBILITY IN WATER: Nil
 SPECIFIC GRAVITY (H₂O = 1): .8545 PERCENT VOLATILE Less than .01%
 EVAPORATION RATE Not determined - believed to be very low. APPROXIMATE BULK DENSITY: _____

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT RANGE: 201°F at 760mmHG (Tag closed cup ASTM D56-79) EXTINGUISHING MEDIA: CO₂, Foam, Dry Chemical. Water no recommended.
 FIRE FIGHTING PROCEDURES: Suitable protective equipment for combating hydrocarbon fires. DOT FLAMMABILITY CLASSIFICATION: _____

UNUSUAL FIRE AND EXPLOSION HAZARDS: This material will not explode spontaneously.

SECTION V - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Flush eyes with large amounts of water.

SKIN CONTACT: Wash with soap and water.

INHALATION: With excessive inhalation remove to fresh air

INGESTION: If swallowed do not induce vomiting, call physician.

SECTION VI - PHYSIOLOGICAL EFFECTS AND HEALTH INFORMATION

ACUTE EFFECTS Overexposure: Excessive inhalation may cause minimal irritation, drowsiness, headache, and nausea. Prolonged skin contact may cause dermatities. May cause minimal eye irritation.

CHRONIC EFFECTS _____

SECTION VII - REACTIVITY DATA

STABILITY (Conditions to Avoid): Stable.

Keep away from heat and open flames.

INCOMPATIBILITY (Materials to Avoid): Incompatible with strong oxidizing agents such as nitric acid, hydrogen peroxide, and chromic acid.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, combustion products of nitrogen and sulfur.

HAZARDOUS POLYMERIZATION (Conditions to Avoid): Will not occur

SECTION VIII - SPILL OR LEAK PROCEDURES

PROCEDURES IN CASE OF RELEASE OR SPILL: Wipe dry or absorb with suitable material. Do not leave surface slippery. Disposal of rags or other absorbents must be in accordance with Federal, state and local hazardous waste regulations.

WASTE DISPOSAL METHOD: Disposal according to all pertaining hazardous waste regulations.

SECTION IX - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: None required

VENTILATION: Local exhaust. Do not use in closed, confined area.

PROTECTIVE GLOVES: Oil resistant gloves optional

EYE PROTECTION: Precautions should be taken to avoid product from splashing into eyes. Safety goggles or face shield optional.

OTHER PROTECTIVE EQUIPMENT: None.

SECTION X - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORING PRECAUTIONS: Keep away from heat and open flames.

OTHER PRECAUTIONS: None.

SECTION XI - DOCUMENTARY INFORMATION

PRODUCT CODE NUMBER _____

ISSUE DATE _____

REPLACES MSDS NUMBER: _____

PREVIOUS PRODUCT CODE NUMBER: _____

PREVIOUSLY ISSUED: _____