

MATERIAL SAFETY DATA SHEET

(Prepared according to 29 CFR 1910.1200)

Degree of hazard: 4 = Extreme, 3 = High, 2 = Moderate, 1 = Slight, 0 = Insignificant

Health 1
Flammability 0
Reactivity 0**SECTION I: PRODUCT IDENTIFICATION****PRODUCT NAME:** Browning Treatment
DOC CODE: Browning Treatment
CHEMICAL FAMILY: Mixture.
EMERGENCY 24-HOUR TELEPHONE # 1-800-424-9300 (CHEMTREC)
N/A = Not applicable or Not available.**DATE REVIEWED:** April 19, 2002

N/D = Not determined.

SECTION II: COMPOSITION/ INFORMATION ON INGREDIENTS

This product has not been tested as a whole for health effects on animals or humans. According to the OSHA Hazardous Communications Standard (29 CFR 1910.1200) any hazardous ingredients that comprise >1.0% of the material and any carcinogenic ingredients that comprise >0.1% must be listed on the MSDS. When individually tested at 100% ingredients in the make-up of this product posed the following health hazards. This product is used as is.

SECTION II a: HAZARDOUS INGREDIENTS >1.0%

Chemical Name	CAS #	PEL	TLV
Sodium Bisulfite	7681-57-4	5 mg/m ³	5 mg/m ³

SECTION II b: CARCINOGENIC INGREDIENTS AT >0.1%

None.

SECTION III: HAZARDS IDENTIFICATIONEYES: May cause eye irritation.
SKIN: May cause skin irritation.
INHALATION: May cause irritation of the upper respiratory tract.
INGESTION: May cause abdominal discomfort, nausea and diarrhea.**SECTION IV: FIRST AID PROCEDURES**EYES: Flush with water for at least 15 minutes. If irritation persists consult physician.
INGESTION: Drink 1 to 2 glasses of water. Consult physician.
INHALED: Remove to fresh air. If symptoms persist or are severe seek prompt medical assistance.
SKIN: Remove contaminated clothing. Thoroughly wash exposed area with soap and water.
PHYSICIAN: Treatment based on judgment of attending physician.

SECTION V: FIRE AND EXPLOSION DATA

FLASH POINT: N/A

AUTO-IGNITION TEMPERATURE: N/D

EXPLOSIVE LIMITS - UEL: N/D LEL: N/D

EXTINGUISHING MEDIA: Alcohol foam, water fog, CO₂ or dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Use NIOSH/MSHA approved self-contained positive pressure breathing apparatus and protective clothing where this material is involved in a fire.

UNUSUAL FIRE AND EXPLOSION HAZARD: None known.

SECTION VI: ACCIDENTAL RELEASE MEASURES

Soak up spilled material with absorbant clay and dispose according to local, state and federal regulations.

SECTION VII: HANDLING AND STORAGE

DO NOT STORE NEAR ALKALI AND OXIDIZING AGENTS.

SECTION VIII: PROTECTION MEASURES

VENTILATION: Local exhaust or dilution ventilation is necessary in poorly ventilated areas.

GLOVES: Rubber gloves.

RESPIRATORY: Not usually required.

EYE: Safety glasses. Wear splash goggles when mists or aerosols are anticipated.

OTHER PROTECTIVE EQUIPMENT: Body-covering clothing should be worn.

SECTION IX: PHYSICAL/CHEMICAL DATA

APPEARANCE AND ODOR: Clear colorless liquid with sulfite odor.

WATER SOLUBILITY, % BY WT: All proportions.

WT/GAL: 8.5 lbs.

BOILING POINT: N/D

VOLATILE BY WT: 97 - 98

pH: 4.0 - 5.0

SPECIFIC GRAVITY: 1.01 - 1.02

SECTION X: REACTIVITY DATA

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur.

INCOMPATIBILITY: Strong alkali's and oxidizing agents.

HAZARDOUS DECOMPOSITION/COMBUSTION PRODUCTS: Possibly oxides of carbon and other unidentified organic compounds.

SECTION XI: TOXICOLOGICAL INFORMATION OF INGREDIENTS

Sodium Bisulfite: Oral rat LD50 is 2000 mg/kg, Dermal rabbit LD50 is >11000 mg/kg, Inhalation rat LC50 is >5 mg/l.

SECTION XII: ECOLOGICAL INFORMATION

Ready to use solution is biodegradable. No other information is available.

SECTION XIII: SPILL, LEAK AND DISPOSAL PROCEDURES

WASTE DISPOSAL: In accordance with Federal, state and local regulations.

NEUTRALIZING CHEMICALS: Water.

SECTION XIV: TRANSPORT INFORMATION PER 49 CFR 172.101

GROUND TRANSPORTATION:

4/1 GALLON CASE – ORM-D.

55 GALLON DRUM- Bisulfites, aqueous solutions, n.o.s, Class 8, UN2693, PGIII.

AIR TRANSPORTATION:

Bisulfites, aqueous solutions, n.o.s, Class 8, UN2693, PGIII.

Quantity Limitations: 1 L. Aircraft: Passenger.

Quantity Limitations: 25L. Aircraft: Cargo.

MARITIME TRANSPORTATION:

Bisulfites, aqueous solutions, n.o.s, Class 8, UN2693, PGIII.

IMDG PAGE #: 8126.

SECTION XV: REGULATORY INFORMATION

Domestic:

TSCA: All ingredients are listed on the TSCA chemical substance inventory.

SARA Section 313 Ingredients: None.

California Prop 65 Ingredients: None.

International:

European labeling requirements:

Not dangerous for supply.

Canadian product classification:

D2B.

SECTION XVI: OTHER INFORMATION

One should always use chemicals with awareness of potential hazards, known and unknown, and their effect on the human system. We urge users to minimize employee exposure to all chemicals, including this product and to keep the level of exposure commensurate with good industrial hygiene practices.

DISCLAIMER OF LIABILITY

The manufacturer and seller warrants that this product conforms to its standard specifications when used according to directions. As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material and the results to be obtained from the use thereof.

