

# Safety Data Sheet



## 1. Identification

|                             |  |                         |  |
|-----------------------------|--|-------------------------|--|
| <b>Product Name:</b>        | WDCARE QT 6PK WATCO TEAK OIL INT/<br>EXT                                       | <b>Revision Date:</b>   | 8/24/2015  |
| <b>Product Identifier:</b>  | 67141  | <b>Supercedes Date:</b> | New SDS  |
| <b>Product Use/Class:</b>   | No Information   |                         |  |
| <b>Supplier:</b>            | Rust-Oleum Corporation<br>11 Hawthorn Parkway<br>Vernon Hills, IL 60061<br>USA | <b>Manufacturer:</b>    | Rust-Oleum Corporation<br>11 Hawthorn Parkway<br>Vernon Hills, IL 60061<br>USA |
| <b>Preparer:</b>            | Regulatory Department  |                         |  |
| <b>Emergency Telephone:</b> | 24 Hour Hotline: 847-367-7700  |                         |  |

## 2. Hazard Identification

### Classification

### Symbol(s) of Product



### Signal Word

Danger

### GHS HAZARD STATEMENTS

|                                     |      |  |
|-------------------------------------|------|--|
| Flammable Liquid, category 3        | H226 | Flammable liquid and vapor.  |
| Germ Cell Mutagenicity, category 1B | H340 | May cause genetic defects. Classified as mutagenic Category 1 if one ingredient is present at or above 0.1%. Applies to liquids, solids (w/w units) and gases (v/v). The substance may also have its own exposure limit. Routes of exposure are dependent on ingredient form.                            |
| Carcinogenicity, category 1B        | H350 | May cause cancer. Classified as carcinogenic Category 1 on the basis of epidemiological and/or animal data. Mixtures are classified as carcinogenic when at least 1 ingredient has been classified as carcinogenic and is present at 0.1% or above. Routes of exposure are dependent on ingredient form. |
| STOT, repeated exposure, category 1 | H372 | Causes damage to organs.   |

### GHS LABEL PRECAUTIONARY STATEMENTS

|           |  |
|-----------|--|
| P201      | Obtain special instructions before use.  |
| P210      | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P260      | Do not breathe dust, fumes, gases, mists, vapors, or spray.                                    |
| P281      | Use personal protective equipment as required.   |
| P308+P313 | IF exposed or concerned: Get medical advice/attention.   |
| P314      | Get medical advice/attention if you feel unwell.   |

### GHS SDS PRECAUTIONARY STATEMENTS

|      |  |
|------|--|
| P240 | Ground/bond container and receiving equipment.                 |
| P241 | Use explosion-proof electrical/ventilating/lighting/equipment. |

P242  
P243  
P270

Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not eat, drink or smoke when using this product.

### 3. Composition/Information On Ingredients

#### HAZARDOUS SUBSTANCES

| <u>Chemical Name</u>                   | <u>CAS-No.</u> | <u>Wt.% Range</u> | <u>GHS Symbols</u> | <u>GHS Statements</u> |
|--|----------------|-------------------|--------------------|-----------------------|
| Naphtha, Petroleum, Hydrotreated Light | 64742-49-0     | 25-50             | GHS08              | H304                  |
| Stoddard Solvent                       | 8052-41-3      | 10-25             | GHS08              | H304-340-350-372      |
| Solvent Naphtha, Light Aromatic        | 64742-95-6     | 1.0-2.5           | GHS07-GHS08        | H304-332-340-350      |
| Mineral Spirits                        | 64742-88-7     | 1.0-2.5           | GHS08              | H304-372              |
| Methanol                               | 67-56-1        | 0.1-1.0           | GHS02-GHS06-GHS08  | H225-311-331-370      |

### 4. First-aid Measures

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately. If swallowed, get medical attention.

### 5. Fire-fighting Measures

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Closed containers may explode when exposed to extreme heat due to buildup of steam. Keep containers tightly closed. Combustible liquid and vapor. No unusual fire or explosion hazards noted.

**SPECIAL FIREFIGHTING PROCEDURES:** Evacuate area and fight fire from a safe distance. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

### 6. Accidental Release Measures

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers.

### 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

**STORAGE:** Store in a dry, well ventilated place. Keep container tightly closed when not in use. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Do not store above 120 ° F. Store large quantities in buildings designed and protected for storage of NFPA Class II combustible liquids. Avoid excess heat.

### 8. Exposure Controls/Personal Protection

| Chemical Name | CAS-No. | Weight % Less Than | ACGIH TLV-TWA | ACGIH TLV-STEL | OSHA PEL-TWA | OSHA PEL-CEILING |
|---------------|---------|--------------------|---------------|----------------|--------------|------------------|
|               |         |                    |               |                |              |                  |

|  |            |      |         |         |         |      |
|--|------------|------|---------|---------|---------|------|
| Naphtha, Petroleum, Hydrotreated Light | 64742-49-0 | 40.0 | N.E.    | N.E.    | N.E.    | N.E. |
| Stoddard Solvent                       | 8052-41-3  | 15.0 | 100 ppm | N.E.    | 500 ppm | N.E. |
| Solvent Naphtha, Light Aromatic        | 64742-95-6 | 5.0  | N.E.    | N.E.    | N.E.    | N.E. |
| Mineral Spirits                        | 64742-88-7 | 5.0  | N.E.    | N.E.    | N.E.    | N.E. |
| Methanol                               | 67-56-1    | 1.0  | 200 ppm | 250 ppm | 200 ppm | N.E. |

## PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**SKIN PROTECTION:** Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

**EYE PROTECTION:** Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

## 9. Physical and Chemical Properties

|                                 |                     |  |           |
|---------------------------------|---------------------|--|-----------|
| <b>Appearance:</b>              | Liquid              | <b>Physical State:</b>                         | Liquid    |
| <b>Odor:</b>                    | Solvent Like        | <b>Odor Threshold:</b>                         | N.E.      |
| <b>Relative Density:</b>        | 0.862               | <b>pH:</b>                                     | N.A.      |
| <b>Freeze Point, °C:</b>        | N.D.                | <b>Viscosity:</b>                              | N.D.      |
| <b>Solubility in Water:</b>     | Slight              | <b>Partition Coefficient, n-octanol/water:</b> | N.D.      |
| <b>Decomposition Temp., °C:</b> | N.D.                | <b>Explosive Limits, vol%:</b>                 | 0.9 - 7.0 |
| <b>Boiling Range, °C:</b>       | -18 - 316           | <b>Flash Point, °C:</b>                        | 41        |
| <b>Flammability:</b>            | Supports Combustion | <b>Auto-ignition Temp., °C:</b>                | N.D.      |
| <b>Evaporation Rate:</b>        | Slower than Ether   | <b>Vapor Pressure:</b>                         | N.D.      |
| <b>Vapor Density:</b>           | Heavier than Air    |  |           |

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

**CONDITIONS TO AVOID:** Avoid temperatures above 120°F (49°C). Avoid contact with strong acid and strong bases.

**INCOMPATIBILITY:** Incompatible with strong oxidizing agents, strong acids and strong alkalis.

**HAZARDOUS DECOMPOSITION:** When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide, carbon dioxide, and formaldehyde.

**HAZARDOUS POLYMERIZATION:** Will not occur under normal conditions.

**STABILITY:** This product is stable under normal storage conditions.

## 11. Toxicological information

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Substance causes moderate eye irritation.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Substance may cause slight skin irritation.

**EFFECTS OF OVEREXPOSURE - INHALATION:** High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs. Prolonged or excessive inhalation may cause respiratory tract irritation.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Irritating to the nose, throat and respiratory tract. Harmful if swallowed. Poison, may be fatal or cause blindness if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

**ACUTE TOXICITY VALUES**

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| <u>CAS-No.</u> | <u>Chemical Name</u>                   | <u>Oral LD50</u> | <u>Dermal LD50</u> | <u>Vapor LC50</u> |
|----------------|--|------------------|--------------------|-------------------|
| 64742-49-0     | Naphtha, Petroleum, Hydrotreated Light | >5000 mg/kg Rat  | >3160 mg/kg Rabbit | N.I.              |
| 64742-95-6     | Solvent Naphtha, Light Aromatic        | N.I.             | >2000 mg/kg Rabbit | N.I.              |
| 64742-88-7     | Mineral Spirits                        | >5000 mg/kg Rat  | 3000 mg/kg Rabbit  | 4951 mg/L Rat     |
| 67-56-1        | Methanol                               | 5628 mg/kg Rat   | N.I.               | 83.2 mg/L Rat     |

N.I. - No Information

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components.

## 13. Disposal Information

**DISPOSAL INFORMATION:** Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

## 14. Transport Information

|                              | <u>Domestic (USDOT)</u> | <u>International (IMDG)</u> | <u>Air (IATA)</u> | <u>TDG (Canada)</u> |
|------------------------------|-------------------------|-----------------------------|-------------------|---------------------|
| <b>UN Number:</b>            | N.A.                    | 1263                        | 1263              | N.A.                |
| <b>Proper Shipping Name:</b> | Not Regulated           | Paint                       | Paint             | Not Regulated       |
| <b>Hazard Class:</b>         | N.A.                    | 3                           | 3                 | N.A.                |
| <b>Packing Group:</b>        | N.A.                    | III                         | III               | N.A.                |
| <b>Limited Quantity:</b>     | No                      | Yes, >5L No                 | Yes, >5L No       | No                  |

## 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| Methanol             | 67-56-1        |

#### Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

**16. Other Information****HMIS RATINGS**

Health: 2\*      Flammability: 2      Physical Hazard: 0      Personal Protection: X

**NFPA RATINGS**

Health: 2      Flammability: 2      Instability: 0

VOLATILE ORGANIC COMPOUNDS, g/L: 450

SDS REVISION DATE: 8/24/2015

**REASON FOR REVISION:**

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.